



FOOD GRADE SILICONE LUBRICANT



LUTM210

- 
Light Pressure Lubricant
- 
NSF[®] Registered; H2 Rated (Lubricants with no contact) (Registration # 115089)
- 
Minimum - Maximum operational temperature range: Low -40 °F (-40 °C) • High 450 °F (232 °C)
- 
5% Silicone
- 
Features Spray AnywayTM nozzle
- 
HMS Hazard Rating: Health (2) • Flammability (4) • Reactivity (0)

- Meets FDA regulations
- Safe on styrene and urethanes
- Stops sticking without transfer




PRESERVE. PROTECT. PREVENT.TM

Sprayon[®] LUTM210 Food Grade Silicone Lubricant is a 5% low-viscosity silicone formula that is compatible with most surfaces. Meets FDA regulation described in Title 21 paragraph 178.3570, when no more than 1 ppm is imparted. NSF H1 rated for use in federally-inspected meat and poultry plants. Effective from -40°F to +450°F. Repels water and is non-corrosive to metals. An excellent lubricant on plastic, fiber gears, extruded parts, wood-to-wood sliding applications and on rubber.

LUBRICANTS

USES

- Slides
- Food and drug processing equipment
- Guides
- Knives
- Food racks
- Slicers
- Heat sealing equipment
- Saws
- Overhead drives
- Grinders
- Belts
- Mixers
- Bottling machines
- Conveyors
- Chutes



LU210

© 2010 Sprayon® Products Made in U.S.A.

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature (70F.) Shake well before using. Spray at a distance of 10" to 14" from surface.

PERFORMANCE

PLASTIC SAFE: Yes
TEMPERATURE RANGE:
LOW: -40°F
HIGH: 450°F
LOAD CAPACITY: Light

- NSF Registration Number 115089, H1 Rated
- Penetrant
- Water-Displacer
- Rust Inhibitor
- Equipped with SPRAY ANYWAY™ valve
- Equipped with an extension tube for hard-to-reach areas

PACKAGING

Stock #: S00210
UPC Code: 0-75577-90210-1
Fill Wt.: 10 oz.
Per Case: 12
Carton Dimensions:
L 11.13" x W 8.44" x H 8.38"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

PHYSICAL

APPEARANCE: Clear liquid
ODOR: Slight solvent
PROPELLANT: Hydrocarbon
WT./GAL.: 5.42
SPECIFIC GRAVITY: 0.65
VISCOSITY: Low
PAINTABLE: No
% VOC AEROSOL: 95.00%
V.O.C. COMPLIANT CALIFORNIA: Yes
V.O.C. COMPLIANT OTC STATES: Yes
FLAMMABLE: Yes
FLASH POINT: <0°F
HAZARD RATING: 2,4,0
SHELF LIFE: 3 years from date of manufacture

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:
sprayon.com
CUSTOMER SERVICE:
1-800-777-2966
TECHNICAL INFORMATION:
1-800-251-2486



Distributed by:

Lawson Products, Inc.

To order these and other products, contact us:

866-529-7664 lawsonproducts.com

PRESERVE. PROTECT. PREVENT.



Sprayon® Products
101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

310-PDS-LU210