

Technical Data Sheet

Lube Ease FG White Grease



Overview

A multi-purpose, high purity food grade lubricant that provides long lasting grease protection. Withstands heat to 500°F. Temperatures above 400°F may require periodic reapplication. NSF rated H1.

Features/Benefits

- Resists extreme pressure, corrosion & water washout
- Temperature range of -40° – 500°F
- Reduces friction & wear
- Resists throw-off
- Calcium sulfonate based

Applications

For use by bakeries, bottlers, breweries, canneries, dairies, egg processors, meat and poultry processors, pharmaceutical manufacturers and food processing and packaging plants.

Method of Application

Catridge

Identification

Food Grade, White Grease

Size


Available in 14 oz. cartridges (10/case), 35 lb. pails and 120 and 400 lb. drums.

Directions for Use

Pump in new grease until old grease comes out. Remove old grease if possible. For ball type grease fittings, fill until old grease comes out. Clean exposed areas with degreaser to remove old grease.

Technical Specifications

- COLOR: White
- THICKENER: Calcium Sulfonate
- NLGI GRADE: 2
- PENETRATION: 265-295
- DROPPING POINT: 550°F
- TEMPERATURE RANGE: -40°F – 500°F
- TIMKEN OK LOAD: 60 lbs.
- BASE OIL: Mineral Oil
- VISCOSITY N/A
- NSF RATING: H1
- FOUR BALL EP LOAD: 620 kg



Caution

Keep out of reach of children. May cause irritation to eyes. Prolonged contact with skin may cause irritation. If ingested, may cause nausea, vomiting, and diarrhea. For eye contact, flush with water, see physician if oily film persists. For skin, wash with soap and water. For ingestion of more than 8 ounces contact physician.

HEALTH	0
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	A

