

THE PROTECTOR™ ALL-PURPOSE LUBRICANT



LU™ 711



Light Pressure Lubricant




NSF® Registered; H2 Rated (Lubricants with no contact) (Registration # 115051)



Dielectric strength value: 47,000 Volts



Minimum - Maximum operational temperature range: Low -20 °F (-29 °C) • High 500 °F (260 °C)



Flash Point: 140 °F (60 °C)



Features Spray Anyway™ nozzle



HMIS Hazard Rating: Health (2) • Flammability (3) • Reactivity (0)

- Penetrates/prevents rust
- Displaces moisture/lubricates
- Contains no silicone




PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™711 The Protector™ All-Purpose Lubricant is an ultra-thin, transparent blend of high-quality petroleum distillates specifically formulated to ensure maximum moisture displacement. Its film resists the collection of abrasive particles on delicate contacts and connectors. The superior qualities of LU™711 form a continuous film that spreads evenly over metal surfaces, giving uniform protection against corrosion attack. This 'spreadability' also makes LU™711 an excellent penetrant for freeing corroded parts and mechanisms. Will not affect plastic, rubber, fabrics or painted surfaces.

LUBRICANTS

USES

- All metal surfaces
- Nuts and bolts
- Operating controls
- Electrical wiring
- Ignition Systems
- Circuitry
- Connectors



LU711

© 2010 Sprayon® Products Made in U.S.A.

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature (70F.) Shake well before using. Spray at a distance of 10" to 14" from surface.

PERFORMANCE

- DIELECTRIC STRENGTH: 47,000 volts
- PLASTIC SAFE: Yes
- TEMPERATURE RANGE:
 - LOW: -20°F
 - HIGH: 500°F
- LOAD CAPACITY: Light
- NSF Registration Number 115051; H2 Rated
- Penetrant
- Rust Inhibitor
- Meets performance requirements of MILC-23411 and Naval Ordnance Systems Weapons Spec WS-14138.
- Displaces moisture
- Will not attack any ferrous and non-ferrous metals, including aluminum and magnesium
- Exceeds 100 hours of salt spray (ASTM-B-117)
- Humidity resistance -No traces of corrosion after 500 hours exposure (Fed. Std.#791) Method 5329
- Equipped with an extension tube for hard-to-reach areas

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:

sprayon.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486

PROPERTIES

- APPEARANCE: Light amber
- ODOR: Low
- PROPELLANT: CO2
- WT./GAL.: 6.78
- SPECIFIC GRAVITY: 0.82
- PAINTABLE: Yes
- H.A.P.S. (Hazardous Air Pollutants): No
- % VOC BULK: 74.90%
- V.O.C. COMPLIANT CALIFORNIA: Yes
- V.O.C. COMPLIANT OTC STATES: Yes
- FLAMMABLE: Yes
- FLASH POINT: 140°F
- HAZARD RATING: S00711 - 2,4,0
- SHELF LIFE: 3 years from date of manufacture

PACKAGING

Stock #: S00711

UPC Code: 0-75577-90711-3

Fill Wt.: 11 oz.



Per Case: 12

Carton Dimensions:

L 10-7/8" x W 8-3/16" x H 8"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



Distributed by:

Lawson Products, Inc.

To order these and other products, contact us:
866-529-7664 lawsonproducts.com

PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

310-PDS-LU711